

Configure Microsoft 365 or Office 365 send connector (SMTP) for Vaultastic

Table of Contents

[Overview](#)

[Steps to configure an Office 365 send connector \(SMTP connector\)](#)

Overview

Configure Microsoft 365 or Office 365 send connector (SMTP connector) to archive emails to Vaultastic. If you already have this send connector set up, you can skip this step.


Repeat this step for each of your Microsoft 365 or Office 365 email domains for archiving emails to Vaultastic. The Microsoft 365 or Office 365 send connector (SMTP connector) for each domain will have to be configured using the journal id of the corresponding Vaultastic domain.

Steps to configure an Office 365 send connector (SMTP connector)

Log in to the Microsoft 365 or Office 365 admin interface using valid admin credentials.


Search for and **navigate to the Admin Center**

Access the **Exchange Admin Center**




In the **Mail flow** section, select **Connectors**

Click on **Add a Connector**




The connector is used to deliver mail from O365 to Vaultastic. Therefore,

- the **Connection From** has to be **Office 365**
- and the **Connection To** has to be **Your Organization's email server**




Give an **appropriate name and description** to the connector

- Enter **Name**
- Enter **Description**.
- In the **What do you want to do after connector is saved**,
 - Select **Turn it on**
 - Select **Retain internal Exchange email headers**
- Click **Next**




We want to route only the mail meant for the Vaultastic domain via this connector. To configure,

- Select **Only when email messages are sent to these domains**.
- In the **edit box** below, enter the **name of your Vaultastic domain**.
- Click on the **+**
- Click **Next**




Route all the mails to o365-v4.vaultastic.com (<https://o365-v4.vaultastic.com>)

- Enter **o365-v4.vaultastic.com** (<https://o365-v4.vaultastic.com>) in the edit box
- Click on **+**
- Click **Next**




Define the **Security restrictions** for the connector. Always use the secure Transport Layer

- Check the **Always use Transport Layer Security (TLS) to secure the connector**
- For certificate, choose **Any digital certificate, including self-signed certificates**.



Validate the connection by asking M365 to send a test mail to `journal@<your Vaultastic domain>`.

- Enter the `journal@<your vaultastic domain>` in the edit box
- Click **+**
- Click **Validate**



On Validation, click **Next**.

You will be taken to the last stage to **Review the connector**.

Review the settings and select Save.

You will see the defined connector in the list of connectors.

Exchange admin center

Search (Preview)

+ Add a connector Refresh 17 items Search

Status ↑	Name	From	To
Off	VV4 Staging IP mithiconnectx.org	O365	Your org
Off	Vaultastic V4 SMTP connector domain-connectserve...	O365	Your org
Off	VV4 Staging IP connectserver.co.in	O365	Your org
Off	VaultasticV4 Live Server connectserver.co.in	O365	Your org
Off	VV4 connectserver.co.in_Test_2020/12/30 18:38:27	O365	Your org
Off	new connector connectserver.co.in sending to mithi	O365	Your org
Off	o365 to vaultastic connector 2	O365	Your org
On	Receive connector for connectserver.co.in	Your org	O365
On	Receive connector for Skyconnect	Your org	O365
On	receive connector for datafix.com	Your org	O365
On	datafix_vaultastic_send_connector_	O365	Your org
On	datafix.com sending mail to mithi	O365	Your org
On	connectserver_send_connector	O365	Your org
On	mithi_biz_vaultastic_new_connector	O365	Your org

Windows taskbar: Search, ENG IN, 14:12, 25-09-2023